



Announcing the UPS-Shippable Xpress E & Q

Xpress-Q-11A

Digital Automatic
Interior 6" deep,
5 3/4" wide x 6 1/4" high

2011 South Town East Blvd.
Mesquite, Texas
75149-1122
800-876-4328
972-288-7557
Toll Free Fax 888-222-6450
www.paragonweb.com
paragonind@att.net



Xpress-E-9A

Digital Automatic
Interior 9" deep,
8 1/2" wide x 4 1/2" high



Except for the Xpress-E-14A, the new Xpress E and Q series kilns can now ship by UPS. Enjoy much lower shipping cost and faster service than available for small kilns by truck freight.

The Xpress E and Q series kilns feature a 3-key digital controller in the base. We eliminated the side-mounted switch box of earlier models to make the kilns more compact and easier to ship.

Specially designed cartons and foam padding assure that the kilns will arrive in perfect condition.

The front control panel is tilted for easy operation of the Sentry Xpress digital controller. Because these models no longer have the

side-mounted switch box, they need less table-top space.

The Xpress-Q-11A fires to 2300°F on a common 120 volt outlet. It is ideal for enameling, silver clay, glass jewelry, beads, ceramics, stoneware, and porcelain, and glaze testing. The Xpress E-series are larger and ideal for enameling, silver clay, glass, beads, and low-fire ceramics.

Heating elements, exposed in dropped, recessed insulating firebrick grooves, are easy to replace. Unlatch and open the door with one hand.

No extra stand is needed. The built-in base stays cool even during extended holds.

Xpress-E-10A

Digital Automatic
Interior 9" deep,
8 1/2" wide x 8 3/4" high



Features

- Digital Sentry Xpress with 8 Segment Ramp-Hold, Delay Fire, Hold, Skip Segment & Program Review
- On/off switch
- 2 1/2" insulating refractory firebricks
- Operate the door latch with one hand.
- Elements in dropped, recessed brick grooves are easy to replace.
- Tapered door peephole with steel cover
- Slots in the base help dissipate heat.

- Steel floor pan supports the entire brick bottom.
- Electrical components are mounted to a secondary steel base plate away from the firing chamber.
- Durable steel case
- Two year limited warranty
- The Xpress-Q11A, -E-9A and -E-10A conveniently fire on a 120 volt 5-15R outlet.
- The Xpress-E-14A is available in 240, 200, or 208 volt.

Xpress-E-14A

Digital Automatic
Interior 13 1/2" deep,
13" wide x 8 3/4" high



INNOVATIVE
KILNS
since
1948

Note: The Xpress-E-14A is not UPS capable.

Specifications

Kiln Model	Volts	Max. Temp. °F	Firing Chamber Opening	Depth	Cubic Feet	Approx. Shpg. Weight	Outside Dimensions W. x D. x H.	Amps	Watts	NEMA Config.
Xpress-Q-11A	120	2300°	5 3/4" W x 6 1/4" H	6"	.14	35	11" x 14 1/4" x 16 3/4"	12	1,440	5-15R
Xpress-E-9A	120	2000°	8 1/2" W x 4 1/2" H	9"	.19	45	14" x 17 3/4" x 14 3/4"	9	1,100	5-15R
Xpress-E-10A	120	2250°	8 1/2" W x 8 3/4" H	9"	.39	80	14" x 17 1/2" x 19 3/4"	14	1,680	5-15R
Xpress-E-14A	240	2000°	13" W x 8 3/4" H	13 1/2"	.88	115	18 1/4" x 22 1/2" x 20 1/2"	13	3,120	6-20R