



Anneal beautiful beads in the BlueBird Series



BlueBird Jr
Digital Automatic
Ceramic Fiber
Firing Chamber: 6" deep,
13" wide, 2 3/4" high
1 Door: 2" x 13"

The BlueBird kilns are equipped with a user-friendly 3-key Sentry Xpress digital controller. It holds the annealing temperature that you program for the length of time needed.

The standard BlueBird has a ceramic fiber firing chamber; the XL version has an insulating firebrick floor and walls. The element in both kilns is embedded in the roof between layers of ceramic fiber board to reduce dust.

The BlueBird XL now comes with two types of doors: a 10" x 4" short door and a 10" x 4 1/4" tall door. The 10" x 4" short door has a 1/2" gap under the door and includes a double mandrel holder. Place bead rods on the mandrel holder, which cradles the rods at two points. Because of the gap, the door remains closed even with bead mandrels in the kiln. Adjust the height of the mandrel holder by loosening screws underneath.

To save table space, the Sentry Xpress digital controller is mounted under the kilns in an ergonomic sloped panel for easy operation. The kilns plug into a standard household outlet and ship by convenient UPS.



BlueBird
Digital Automatic
Ceramic Fiber
Firing Chamber: 6" deep,
20" wide, 2 3/4" high
2 Doors: 2" x 10"

Side latches hold the doors closed while heating to annealing temperature. Plastic knobs on the door handles stay cool to the touch. Rare-earth magnets hold the doors open when needed.

BlueBird & BlueBird Jr Features

- 3-key digital Sentry Xpress controller
- Stainless steel glass rod warmer
- Ceramic fiber roof, walls, and floor
- Roof element embedded between layers of ceramic fiber board to reduce dust.
- BlueBird doors: 2, each 10" wide, 2" high, 1" thick ceramic fiber
- BlueBird Jr single door: 2" x 13"
- Mandrel holder
- 1200°F maximum temperature
- Mar-proof plastic feet
- On-off safety switch
- Door latches

BlueBird XL Features

- 3-key digital Sentry Xpress controller
- Stainless steel glass rod warmer
- Firebrick walls and floor



BlueBird XL
Digital Automatic
Firebrick
Firing Chamber: 9" deep,
20" wide, 4 1/2" high
Short door: 4" x 10"
Tall door: 4 1/4" x 10"

- Roof element embedded between layers of ceramic fiber board to reduce dust.
- Short door: 10" wide x 4" high, 1" thick
- Tall door: 10" wide x 4 1/4" high, 1" thick
- Short door is on the left; tall door is on the right.
- Customize your kiln: Order it with 2 short doors or 2 tall doors at no extra charge.
- Mandrel holder with 20 slots
- 1500°F maximum temperature
- Mar-proof plastic feet
- On-off safety switch
- Door latches

Paragon Industries, L. P.
Better Designed Kilns™
2011 South Town East Blvd.
Mesquite, Texas 75149-1122
800-876-4328 / 972-288-7557
www.paragonweb.com

Kiln Specifications

Kiln Model	Volts	Max. Temp. °F	Firing Chamber Opening	Depth	Cubic Feet	Approx. Shpg. Weight	Outside Dimensions W. x D. x H.	Amps	Watts	NEMA Config.
BlueBird	120	1200°	20"W x 2 3/4"H	6"	.19	48	27" x 15 1/4" x 14 1/2"	12.5	1500	5-15R
BlueBird Jr	120	1200°	13"W x 2 3/4"H	6"	.12	38	20" x 15 1/4" x 16"	6	700	5-15R
BlueBird XL	120	1500°	20"W x 4 1/2"H	9"	.47	86	25 1/2" x 19" x 16"	14	1700	5-15R