



**Better
Designed
Kilns™**

Enjoy a Paragon digital SC-series jewelry kiln

Your jewelry making will evolve when you own a Paragon SC-series kiln. The Sentry Xpress digital controller is easy to use, reliable, and accurate. The kilns ship by convenient UPS.

The digital SC-series kilns fire silver, clay, decals, china paint, enameling, and glass in minutes up to 2000°F. The light-weight, portable SC-series kilns are popular with seminar teachers because they fire so fast, plug into a 120 volt outlet, and are easy to sell.

The SC-series door opens 180 degrees for easy loading. The kilns ship by UPS and are also available for Europe.

The SC-series are surprisingly affordable for digital kilns. They fire automatically at the rate and temperature you enter. A large, brightly lit display prompts for firing rate, temperature and hold time. Use the hold feature to automatically soak any type of clay, silver or gold to its recommended time.

The high-tech, energy efficient ceramic fiber firing chamber is wrapped in a steel inner case. The outer steel case remains cool due to the layer of air between it and the inner case. In addition, the case is slotted for air circulation. Electrical components, located in the base, stay cool for long life even at extended hold times. This is one reason the SC-series kilns are so trouble-free. The long life of a Paragon SC-series kiln is legendary.

The fast firing element is embedded in the firing chamber shell. The SC-2 heats from the two sides. The kiln includes a top vent for lost wax casting, complete with a tapered plug. Each SC-series kiln includes a 1/4" thick ceramic fiber shelf.



Standard SC-2



SC-2 with Window



SC-2 w/ Door & Window

The new SC-1 is designed for traveling. It is small enough to carry even under your arm.

Door Options

Order an SC-2 with an optional bead annealing door, glass window, or both. Watch the interior turn bright red through the glass window. It is 1" x 3" when ordered with the bead annealing door and 2" x 2" without the bead door. (Note: always wear firing safety glasses when viewing the kiln interior.) The glass window is guaranteed up to 2350°F (1260°C).

The SC-1 can be ordered with an optional 1" x 3" window. It is not available with bead door.



SC-2 with Bead Door

Paragon Industries, L.P.

2011 South Town East Blvd.
Mesquite, Texas 75149-1122
800-876-4328 / 972-288-7557
www.paragonweb.com
info@paragonweb.com



Standard SC-1



Standard SC-3

The SC-2 and SC-3 are certified to CSA and UL std 499.

SC-1, SC-2 & SC-3 2010 SPECIFICATIONS

Kiln Model	Volts	Max. Temp. °F	Firing Chamber Opening	Firing Chamber Depth	Cubic Feet	Approx. Shpg. Weight	Outside Dimensions W. x D. x H.	Amps	Watts	NEMA Config.
SC-1	120	2000°	6"W x 3"H	3 3/4"	.04	15	11" x 10" x 12 1/4"	5	600	5-15R
SC-2	120	2000°	8"W x 5 3/4" H	7 3/4"	.19	36	13 1/4" x 14" x 15 1/2"	12	1,440	5-15R
SC-3	120	2000°	7 3/4"W x 7 3/4" H	8"	.28	41	13 1/4" x 14" x 17"	15	1,800	5-15R