



POWER REQ'TS
 240 VOLTS
 1 PHASE
 60 HERTZ
 18 AMPS
 4130 WATTS

CAUTION
 TO PROVIDE CONTINUED PROTECTION AGAINST THE RISK OF ELECTRIC SHOCK, CUSTOMER'S POWER SUPPLY MUST BE PROPERLY GROUNDED.
 NOTE: GROUNDING SCREW TO HAVE A GREEN COLORED SLOTTED AND/OR HEX HEAD NO SUBSTITUTES. USE #1005
 NOTE: THE SURFACE OF THE INSULATED WIRES MARKED (X) TO BE COLORED GREEN, WITH OR WITHOUT ONE OR MORE YELLOW STROPIES.

WIRING NOTE
 ALL WIRES #14 AWG, TYPE SEW/SF2 MINIMUM UNLESS OTHERWISE NOTED

TO RE-ORDER ELEMENTS, SPECIFY		
DESCRIPTION	QTY	LDC
ELS1604-4S	2	SIDES
ELS1604-4T	1	TOP

R/H 1024
 SENTRY 2.0

CFG 5
 BLUE
 2350°F

NOTE: PLEASE REFER TO THIS NUMBER WHEN ORDERING PARTS FOR THIS ILM

REV	DATE	BY	DESCRIPTION
-	8/30/16	DTB	

SWITCH BOX ASSY- 42284-6
 PARAGON INDUSTRIES
 2011 SOUTH TOWN EAST BLVD
 MESQUITE, TEXAS 75149

WIRING DIAGRAM
 240V, 1 PHASE, 60HZ, 4130WATTS

PART NO.	REV
S1604-4	-
KM 11X4X24 DROP DR	FILE