



**CAUTION**

TO PROVIDE CONTINUED PROTECTION AGAINST THE RISK OF ELECTRIC SHOCK, CUSTOMER'S POWER SUPPLY MUST BE PROPERLY GROUNDED.

NOTE: GROUNDING SCREW TO HAVE A GREEN COLORED SLOTTED AND/OR HEX HEAD NO SUBSTITUTES. USE #1005

NOTE: THE SURFACE OF THE INSULATED WIRES MARKED (X) TO BE COLORED GREEN, WITH OR WITHOUT ONE OR MORE YELLOW STRIPES.

**POWER REQ'TS**

240 VOLTS  
1 PHASE  
60 HERTZ  
30 AMPS  
7200 WATTS

**WIRE SIZES**

NOTE: ALL WIRES TO BE TYPE SEW/SF2, #14 AWG MINIMUM UNLESS NOTED

TO RE-ORDER ELEMENTS, SPECIFY		
DESCRIPTION	QTY	LOC
EL3861131T	3	TOP

FUSE #6726 1/2 AMP #20 GA #4609

1020 SENTRY 2.0

PAINTED STEEL CASE  
UL/CUL LISTED

MAX. TEMP.  
2000° F  
N/C

NOTE: PLEASE REFER TO THIS NUMBER WHEN ORDERING PARTS FOR THIS KILN

ORIGINAL ISSUE	DATE	BY	DESCRIPTION
1-3-96	7-16-96	NLV	BY NJM UPDATED DVG
	10-21-98	NJM	CHGD RELAYS, FUSE & CONT XFRMR
	5/17/01	DTB	CHG BD FROM DTC TO SENTRY

SW BOX #40293

PARAGON INDUSTRIES  
2011 SOUTH TOWN EAST BLVD  
MESQUITE, TEXAS 75149

WIRING DIAGRAM  
GL24AD-SEN 1020 TOP-FIRED ONLY  
240V 1PH 60HZ 7200W

PART NO.	3861131	REV	C
By Norm Montesino		FILE	